



## Irrigation Enhancer Specs

<b>2" Low Flow</b>	
Flow Rate	20 - 50 GPM
Length	52-1/2 Inches
Width	16 Inches
Height	13-1/2 Inches
Flange Center	7-1/16 Inches
Weight	208 LBS.
# of Bolts per flange	4
Bolt Size	5/8"
<i>Lengths Can Vary + or -.5"</i>	

<b>2"</b>	
Flow Rate	50 - 125 GPM
Length	60 Inches
Width	16 Inches
Height	12-3/4 Inches
Flange Center	7-5/16 Inches
Weight	210 LBS.
# of Bolts per flange	4
Bolt Size	5/8"
<i>Lengths Can Vary + or -.5"</i>	

<b>3"</b>	
Flow Rate	125 - 250 GPM
Length	60-1/4 Inches
Width	16 Inches
Height	15 Inches
Flange Center	8-3/16 Inches
Weight	270 LBS.
# of Bolts per flange	4
Bolt Size	5/8"
<i>Lengths Can Vary + or -.5"</i>	

<b>4"</b>	
Flow Rate	250 - 500 GPM
Length	64-1/2 Inches
Width	24 Inches
Height	17-1/4 Inches
Flange Center	9/1/2 Inches
Weight	426 LBS.
# of Bolts per flange	8
Bolt Size	5/8"
<i>Lengths Can Vary + or -.5"</i>	

<b>6"</b>	
Flow Rate	500 - 1000 GPM
Length	67 Inches
Width	24 Inches
Height	19-3/4 Inches
Flange Center	10-3/8 Inches
Weight	558 LBS.
# of Bolts per flange	8
Bolt Size	3/4"
<i>Lengths Can Vary + or -.5"</i>	

<b>8"</b>	
Flow Rate	1000 - 1600 GPM
Length	70 Inches
Width	33 Inches
Height	23-3/4 Inches
Flange Center	13-1/4 Inches
Weight	680 LBS.
# of Bolts per flange	8
Bolt Size	3/4"
<i>Lengths Can Vary + or -.5"</i>	

<b>10"</b>	
Flow Rate	1600 - 2500 GPM
Length	60 Inches
Width	33 Inches
Height	26-1/4 Inches
Flange Center	14-1/2 Inches
Weight	868 LBS.
# of Bolts per flange	12
Bolt Size	7/8"
<i>Lengths Can Vary + or -.5"</i>	

<b>12"</b>	
Flow Rate	2500 - 3500 GPM
Length	87 Inches
Width	36 Inches
Height	30 Inches
Flange Center	X
Weight	1410 LBS.
# of Bolts per flange	12
Bolt Size	7/8"
<i>Lengths Can Vary + or -.5"</i>	